

SOCKET (BF)

SDR 11/17, PE2708/PE4710



COSMOIND USA


SOCKET (BF) DIMENSION SHEET

- Manufactured in accordance with AWWA C901 & C906, ASTM D2513 & D3261 & D3350
- Certified to NSF/ANSI 61 and NSF/ANSI-372
- Produced by using a resin listed on the PPI TR-4
- Produced by Injection Molding
- Suitable for Water, Gaseous, Fluids and Slurries
- Excellent chemical resistance and corrosion resistance

(at 73.4 °F)

GRADE	Gas		Industrial	
	SDR17	SDR11	SDR17	SDR11
2708	62.5 psi	100 psi	100 psi	160 psi
4710	80 psi	125 psi	125 psi	200 psi

Unit : inch



DN	SDR	BF SOCKET		Weight (lbs.)	Type	Item Code	
		D	L			Gas	Industrial
½" CTS	11	0.945	1.417	0.02	Injection (Socket)	COSB GCI0700	COSB WCI0700
½" IPS	11	1.102	1.535	0.07	Injection (Socket)	COSB GCI0701	COSB WCI0701
¾" IPS	11	1.339	1.732	0.07	Injection (Socket)	COSB GCI0702	COSB WCI0702
1" IPS	11	1.614	1.929	0.06	Injection (Socket)	COSB GCI0703	COSB WCI0703
1¼" IPS	11	2.047	2.126	0.11	Injection (Socket)	COSB GCI0704	COSB WCI0704
1½" IPS	11	2.520	2.244	0.16	Injection (Socket)	COSB GCI0705	COSB WCI0705
2" IPS	11	3.110	2.559	0.26	Injection (Socket)	COSB GCI0706	COSB WCI0706
2½" IPS	11	3.661	2.677	0.36	Injection (Socket)	COSB GCI0707	COSB WCI0707



The product dimensions may change for quality improvement by manufacturer